

RTS22 Wall switch OPEN/CLOSE

Format 55

The RTS22 wall switch OPEN/CLOSE from the Format 55 series is a battery-operated secwave transmitter.

This complete version of the RTS22 wall switch contains all the components required to be put into operation immediately. The transmitter module, a white frame and a white single rocker "OPEN/CLOSE" are included in the scope of delivery.

If necessary, the wall switch can be used in cover frames from other manufacturers.

Two transmission channels are available. Each channel can control a secwave receiver or a separate function.



RTS22S5002A1-K

Technical specifications

Coding	secwave AES 128-bit encryption Not compatible with Easywave products!
Frequency	868.30 MHz
Channels	2
Range	typically 150 m in good free-field conditions
Power supply	1x 3V-battery, CR2032
Operating modes	2x PULSE
Operation	transmission starts as soon as button is pressed
Operating temperature	-20 °C to +60 °C
Dimensions (W/L/H)	
Mounting plate	71/71/1,8 mm
Cover frame	55/55/9,0 mm
Single rocker	80/80/9,4 mm
Weight	44 g (including battery and cover frame)
Color	white similar RAL 9003

Scope of delivery

- Transmitter module
incl. battery
- Rocker OPEN/CLOSE
- Cover frame
- Mounting plate
- Adhesive pad
- Operating manual

Accessories (optional)

RTS22-ACC-01-01P	Mounting plate, white
RTS22-ACC-05	Cover frame, white

Models

Product number	Description
RTS22S5002A1-K	Wall switch single rocker complete, secwave, 1x OPEN/CLOSE, Format 55, white